AMENDMENTS TO THE CLAIMS

The listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

- 1. (Currently Amended) A system including:
 - a plurality of devices (142,150,152,154,156);
 - administration means (142,118) for allowing selected devices (150,156) to be associated together as a group by providing each device with security data and identification data, the security data of each device being interpretable by each other device within the group, particular modes of communication only being allowed between devices within the group having such security data, and the identification data identifying each device within the group for the purpose of delivering data to that device but not necessarily being recognisable by other devices not in said group; and
 - routing means (110,116) having an external identifier recognisable by devices not in said group for routing communications via a communication medium (140) and for communicating data originating from one device (150) within said group received via said communication medium (140) by means of the external identifier to another device (152) within said group using the identification data.
- 2. (Original) The system of claim 1, comprising a plurality of said routing means.
- 3. (Original) The system of claim 2, wherein said routing means are operable to route said data securely therebetween via said communication medium.
- 4. (Currently Amended) The system of <u>claim 1</u>, any one of the preceding claims, wherein the data is transmitted by IPsec.
- 5. (Currently Amended) The system of <u>claim 1</u>, any one of the preceding claims, wherein the external identifier is a unique public IP address or telephone number.

- 6. (Currently Amended) The system of <u>claim 1</u>, any one of the preceding claims, wherein the identification data comprises a respective local IP address assigned to each device by the administration means.
- 7. (Currently Amended) The system of claim 1, any one of the preceding claims, wherein wherein at least one of the devices comprises a mobile telecommunications terminal and is operable to communicate with an associated one of the routing means via a mobile telecommunications network.
- 8. (Original) The system of claim 7, wherein the routing means includes means for authenticating the mobile terminal.
- 9. (Original) The system of claim 8, wherein the authenticating means is operable to authenticate the mobile terminal using data relating to the subscription of the mobile terminal with the mobile telecommunications network.
- 10. **(Original)** The system of claim 9, wherein the mobile telecommunications terminal includes a smart card storing data for exchange with said authentication means.
- 11. (Currently Amended) The system of <u>claim 7</u>, any one of claims 7 to 10, wherein the mobile telecommunications network is a GSM network.
- 12. (Currently Amended) The system of claim 7, any one of claims 7 to 10, wherein the mobile telecommunications network is a UMTS (3G) network.
- 13. (Currently Amended) The system of claim 7, any one of claims 7 to 10, wherein data is exchanged between the mobile telecommunications terminal and the routing means by a GPRS link.

- 14. (Currently Amended) The system of <u>claim 1</u>, any one of the preceding claims, wherein data is exchanged between the mobile telecommunications terminal and the routing means using Session Initiation Protocol (SIP).
- 15. (Currently Amended) The system of <u>claim 2</u>, any one of <u>claims 7 to 10</u>, wherein the routing means are operable to exchange external identifiers therebetween.
- 16. (Currently Amended) The system of <u>claim 2</u>, any one of <u>claims 7 to 10</u>, including means for generating an IP address for enabling communications to be routed between respective ones of the routing means.
- 17. (Currently Amended) The system of <u>claim 1</u>, any one of the preceding claims, wherein each device stores a key.
- 18. (Currently Amended) The system of <u>claim 1</u>, any one of the preceding claims, wherein the routing means is operable to generate a public-private key pair.
- 19. (Currently Amended) The system of claim[[s]] 17 and 18, wherein the device associated with the routing means is operable to generate a certificate using the public key of the routing means and the device's key.
- 20. (Original) The system of claim 19, wherein the routing means is operable to authenticate itself with the administration means using said certificate.
- 21. **(Original)** A method of configuring an IP address to allow data exchange between a first device "A" and a second device "B" that are associated with one another in a group, the group having a group identifier "Group-ID", and each device having unique identifier "Group-Member-ID" within the group, and where the devices are coupled to one another for communication therebetween via respective communication hubs "Hub-A" and "Hub-B", the method including providing each of said devices with a unique IP address within said group.

22. (Original) The method of claim 21, including:

allocating a range of IP addresses as follows: first octet of the IP address=10 (Fixed).X.Y.Z; where X,Y,Z is calculated as follows:

X = [Hash(Group-ID)][0,1,2...15],

Y = [Hash(IDn)][7,8,...15]

Z = [Hash(Group-Member-ID)][0,1,2....7];

where the IDn is either Group-Member-ID or an identifier of a device acting as a gateway device for a plurality of the devices,

where the final IP address=10.X.Y.Z, and where "Hash" is a hash function.

- 23. (Original) The method of claim 22, wherein "Hash" is a MD5 algorithm.
- 24. (Currently Amended) A method of enabling communication between a plurality of devices (142,150,152,154,156), the method including associating selected devices (150,152) together as a group by providing each device (150,152) with security data and identification data, the security data of each device being interpretable by each other device within the group, particular modes of communication only being allowed between devices within the group having such security data, and the identification data identifying each device within the group for the purpose of delivering data to that device but not necessarily being recognisable by other devices not in said group; and routing data originating from one device (150) within said group by routing means (110,116), having an external identifier recognisable by devices not in said group for routing communications via a communication medium (140), which communicates that data received via the communication medium (140) by means of the external identifier to another device (152) within said group using the identification data.
- 25. (Original) The method of claim 24, including providing a plurality of said routing means.
- 26. (Original) The method of claim 25, wherein said routing means route said data securely therebetween via said communication medium.

- 27. (Currently Amended) The method of <u>claim 24</u>, any one of claims 7 to 10, wherein the data is transmitted by IPsec.
- 28. (Currently Amended) The method of <u>claim 24</u>, any one of claims 7 to 10, wherein the external identifier is a unique public IP address or telephone number.
- 29. (Currently Amended) The method of <u>claim 24</u>, any one of <u>claims 7 to 10</u>, wherein the identification data comprises a respective local IP address assigned to each device.
- 30. (Currently Amended) The method of claim 24, any-one of the preceding claims, wherein at least one of the devices comprises a mobile telecommunications terminal which communicates with an associated one of the routing means via a mobile telecommunications network.
- 31. (Original) The method of claim 30, wherein the routing means authenticates the mobile terminal.
- 32. (Original) The method of claim 31, wherein the mobile terminal is authenticated using data relating to the subscription of the mobile terminal with the mobile telecommunications network.
- 33. (Original) The method of claim 32, wherein a smart card associated with the mobile telecommunications terminal stores data to perform said authentication.
- 34. (Currently Amended) The method of claim 30, any one of the preceding claims, wherein the mobile telecommunications network is a GSM network.
- 35. (Currently Amended) The method of <u>claim 28</u>, any one of the preceding claims, wherein the mobile telecommunications network is a UMTS (3G) network.

- 36. (Currently Amended) The method of claim 30, any one of the preceding claims, wherein data is exchanged between the mobile telecommunications terminal and the routing means by a GPRS link.
- 37. (Currently Amended) The method of <u>claim 24</u>, any one of the preceding claims, wherein using Session Initiation Protocol (SIP).
- 38. (Currently Amended) The method of <u>claim 25</u>, any one of the preceding claims, wherein respective ones of the routing means exchange external identifiers therebetween.
- 39. (Currently Amended) The method of <u>claim 25</u>, any one of the preceding claims, including generating an IP address for enabling communications to be routed between respective ones of the routing means.
- 40. (Currently Amended) The system of <u>claim 24</u>, any one of the preceding claims, wherein each device stores a key.
- 41. (Currently Amended) The system of <u>claim 24</u>, any one of the preceding claims, wherein the routing means generates public-private key pairs.
- 42. (Currently Amended) The method of claim[[s]] 40 and 41, wherein the device associated with the routing means generates a certificate using the public key of the routing means and the device's key.
- 43. (Original) The method of claim 42, wherein the routing means authenticates itself within the group using said certificate.
- 44. (Currently Amended) A routing node (118) for enabling communication between a plurality of devices (142,150,152,154,156)—which are associated together as a group by providing each device with security data and identification data, the security data of each device being interpretable to each other device within the group, particular modes of communication

only being allowed between devices within the group having such security data, and the identification data identifying each device within the group for the purpose of delivering data to that device but not necessarily being recognisable by other devices not in said group; wherein the routing node (118) has an external identifier recognisable by devices not in said group for routing communications via a communication medium (140), and communicates data originating from one device (150) within said group received via said communication medium (140) by means of the external identifier to another device (152) within said group using the identification data.

- 45. (Currently Amended) The system of <u>claim 1</u>, method or routing node of any one of the preceding claims, wherein the communication medium comprises the Internet.
- 46. **(New)** The method of claim 24, wherein the communication medium comprises the Internet.
- 47. **(New)** The method of claim 44, wherein the communication medium comprises the Internet.